

Truck
Isotherm Fridges

32L Compressor Fridge/Freezer

Webasto is excited to announce the addition of a 32Ltr Cooler Box from Indel into their product line of comfort solutions for the Truck market.

The unit runs on a Danfoss BD-35F compressor, with multiple voltage DC 12/24V and AC 115/230V with auto select, and is complimented with a 3 stage battery protection feature.

The unit's thermostat temperature ranges from -16°C to +5°C with both an energy saving function (ECO) and Turbo function (MAX).

With dimensions of 380x350x585mm and weighing 16kg, the unit comes complete with an insulation bag and a 3 year Australian wide warranty, making it the perfect addition to any truck cab.

Features & Benefits:

- 32L capacity
- Simple to use electronic control
- Electronic Thermostat with ECO and Turbo (Max) functions
- Thermostat temperature range +5°C to -16°C
- Danfoss BD-35F Compressor
- CFC free R134a Refrigerant
- Multiple voltage—DC12/24V and AC 115/230V with Auto select
- 3 stage battery protection
- Low power consumption
- Interior light
- Robust design using CFC free insulation
- Insulated carry bag available
- Mounting kit available
- 3 year Australia-wide warranty



Thermostat Control

The electronic thermostat fitted to the TB32A is a new innovation. In addition to the usual functions of temperature regulation and "On/Off" switch, it contains two (2) other major features:

1. Energy Saving Function (ECO)
2. Turbo Function (MAX)

Energy Saving Function (ECO): is manually activated and is useful when the fridge is not being used for a period but still has food and drink inside. When the ECO function is activated the electronic thermostat allows the inner temperature to increase by 5°C above the set temperature. At the same time the compressor speed is reduced to 2000rpm, which results in a significant energy saving. The ECO does not work with temperatures under 0°C.

Turbo Function (MAX): is automatically activated when the inside temperature rises more than 5°C above the thermostat setting. The compressor speed is increased to 3000rpm to reduce the temperature back to the thermostat setting.



Technical specifications:

Unit	Gross Capacity	Installed Power	Dimensions H x W x D (mm)	Weight (kg)	Thermostat Regulation	Refrigerant (CFC-free)
12 / 24V DC 115/230V AC	32 Litre	60W	380 x 350 x 585	16	+5°C / -16°C	R134a

Webasto - Comfort in Mobility

Webasto Product Australia Pty Ltd
Global Comfort Solutions
423-427 The Boulevard
Kirrawee NSW 2232
Australia
Phone: +61 (0)2 8536 4800
Fax: +61 (0)2 8536 4899
info@webasto.com.au

Advice · Installation · Service